



BioLogic Renew Floor

100% Epoxy Resurfacer

DESCRIPTION

BioLogic Renew Floor is a specially designed kit containing epoxy resins, activator, and graded inert aggregates that, when mixed together, make a high quality, self-leveling epoxy floor topping that can be spread to cover approximately 50 square feet at one-eighth (1/8) inch thickness. Gives old, worn floors a new seamless, abrasion resistant, skid free surface that resists acids, alkalis, solvents, heat and cold. BioLogic Renew Floor is also the perfect product for repairing pitted, cracked or damaged epoxy-coated floor surfaces.

FEATURES

- Self-leveling
- 100% epoxy solids
- Highly chemical resistant
- Available in a variety of colors
- Color match available for patching existing epoxy-sealed floors
- Easy to use
- Single kit covers 50 sq. ft. at 1/8"
- Master kit covers 250 sq. ft. at 1/8"

HOW TO USE

New concrete floors should be clean, dust free and at least 28 days old. Older floors should be cleaned and texturized by mechanical means (sand blasting or scabbling) or acid etch. BioLogic Renew Floor is supplied in pre-measured kits - do not add solvent or thinners and use entire contents of cans. For best results, mix base component and activator until a uniform color is obtained. Slowly add aggregate and mix 3-5 minutes until homogenous. Pour the mixed material onto substrate and level to 1/8" with a squeegee or a screed trowel. Do not overwork, but spread evenly with firm strokes. Immediately after spreading, the floor should be firmly rolled with a porcupine Roller which aids in leveling and removing trapped air bubbles.

SPECIFICATIONS

	Part A	Part B	Part C
Physical Form	clear/light viscous liquid	liquid	granules
Color	amber	colored	tan
Odor	acrylate	amine	none
Specific Gravity	1.13	1.00	70 lbs/ft
Flash Point	200° F+	200°F+	none

HMIS SYMBOL

Health	2	3	1
Flammability	1	1	0
Reactivity	0	1	0