

**BioLogic Chemical Works** P.O. Box 82501 Rochester, MI 48308 248.941.0347 ï 248-310.0334

# **LOGICON-WB**

# WATER EMULSION URETHANE SEALER

# **DIRECTIONS**

On smooth concrete, it is desirable to acid etch floor. Rinse thoroughly and allow to dry. Floors must be clean and dry. Apply with a lamb's wool applicator. Place LOGICON in a shallow pan, dip the applicator into the finish. FLOW ON IN THIN COATS. Spread evenly. Dries to touch in 2-4 hours, dries hard in 5-8 hours when applied in thin coats. Allow 24 hours for last coat to dry before using floor. LOGICON dries to an attractive satin finish that needs no buffing. Always ventilate room for guicker hard dry. Keep container tightly closed. COVERAGE: Approximately 500 sq. ft. per gallon.

#### **HMIS**

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0

SEVERE 4 EXTREME SERIOUS 3 HIGH MODERATE 2 MODERATE

SLIGHT 1 SLIGHT

MINIMAL 0 INSIGNIFICANT

LOGICON is a penetrating sealer and conditioner that protects terrazzo and concrete against wear, stains, grease and extraneous moisture. LOGICON penetrates and seals in one easy operation by incorporating a durable film within the concrete that creates adhesions between the aggregate and cementitious material. LOGICON prevents efflorescense or "blooming".

LOGICON is slip resistant and quick drying, with a clear satin finish that does not yellow with age. LOGICON prevents dusting and controls moisture vapors in existing floors while making concrete and terrazzo acid, alkali, oil, grease, soap and water resistant.

# SLIP RESISTANT

**CLEAN SATIN FINISH DOES NOT YELLOW** RESISTS ACID, ALKALI, OIL, GREASE, SOAP, AND WATER

**HELPS OVERCOME UNEVEN POROSITY ON TERRAZZO** 

COVERAGE: APPROXIMATELY **500 SQ. FT. PER GALLON** 

For Industrial and Institutional Use Only The Logical choice for Maintenance Solutions

# **PRECAUTIONS**

LEASE REFER TO THE MSDS SHEETS FOR **PRECAUTIONARY** MORE DETAILED MEASURES, HANDLING INSTRUCTIONS **AND EMERGENCY PROCEDURES.**Contains Acrylic Polymer CAS #9003-01-4. Ethylene Glycol Monobutyl Ether CAS #111-76-2, and Alkyd Resin CAS #51-79-6. Can cause irritation to eyes and skin. Wear protective clothing and wash thoroughly after using. Vapors harmful. Avoid inhalation of vapors. Always use with adequate ventilation or respiratory protection. Harmful if swallowed. Do not take internally. Keep container closed when not in use.

# **FIRST AID**

EYES: flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation. **SKIN:** flush with water and then wash with soap and water. Launder contaminated clothing before reuse. Get medical attention if irritation persists. INHALATION: remove to fresh air and assist breathing as necessary - get medical attention. **INGESTION**: Give water and get medical attention immediately.