



Peel Off

Peelable Coating

DESCRIPTION

Peel Off White Peelable Coating is a thickened protective coating to protect walls and floors of paint spray booths and other areas from overspray. After drying, Peel Off leaves an elastic peelable film that prevents materials from bonding to or contaminating the protected surface, and also offers protection from minor scratches.

FEATURES

- Peelable
- Use on non-porous surfaces
- Build up any film thickness with multiple coats
- Protects surface from minor scratches
- Dries in 15-20 minutes at 70° F

HOW TO USE

Apply to walls and/or floors manually or by airless sprayer. At 5.5-6 mils WFT, cure time is approximately 1 hour. To remove, simply loosen one edge and pull, peeling the material off in a sheet. Use on non-porous surfaces. If spraying on, use pressure feed spray equipment with an air atomizing nozzle to achieve best results. Peel Off can be applied using any existing spray equipment, including suction feed guns and airless sprayers. Good results have been achieved using a Binks Mach 1 Plus 92 x 95P spray gun with a 0.046 fluid nozzle #54-3635. Use 6 psi fluid pressure and 9 psi atomizing air pressure (55-65 psi at handle).

SPECIFICATIONS

Physical Form	Thick liquid
Color	White
Odor	amine
Specific Gravity	1.125
Flash Point	none to boiling

HMIS SYMBOL

Health	1
Flammability	0
Reactivity	0

The logical choice for maintenance solutions

P.O. Box 82501 • Rochester, MI 48308 • 248-941-0347 • Fax 248-941-0347